




1. Front head curtain
2. Front side curtain
3. Brace
4. Spring
5. Water drainage duct
6. Reflective white guide stripe
7. Rubber cord



ADVANTAGES



Drainage system



Tear and wear resistant material

RETRACTABLE DOCK SHELTER

DOORHAN®

Retractable shelters of DSHRT and DSHRTM series are designed to perfectly suit warehouses, logistics centres and other premises with medium cargo traffic. PVC fabric used for front curtains is highly elastic and wear and tear resistant. Trailers back into the shelter during loading/unloading operations while head and side curtains create a tight seal against the truck top and rear body. In case of off-center parking the collapsible frame retracts upon impact and automatically returns to its original position after truck departure. The shelter is mounted using the suspended method of installation.

ACCESSORIES



Corner bag



Rubber



Wheel guides



Shock column

SPECIFICATION	
Width (mm)	3000 / 3400
Height (mm)	3000 / 3400 / 4400
Lip Length (mm)	600 (900 - option)
Thickness of front PVC sheet	3 mm
Thickness of side PVC sheet	0.5 mm
Operating Temp	-35 °C to +50 °C

OPERATION

- >> Only qualified personnel acquainted with the design and construction of the shelter should handle it.
- >> Prior to mounting carefully inspect the dock shelter. Never use it in case any damage is found.
- >> Position the trailer in the middle of the dock shelter aligning with the white guide stripes.
- >> Back the trailer slowly till it contacts with dock bumpers.
- >> Make sure the truck is stationary, the handbrake is put on, the wheels are chocked. Head and side curtains should tightly wrap the truck.
- >> Attention! To prevent dock shelter damage truck size should correspond to shelter type and dimensions.

